



VAN MEDEVOORT

CT260

CD TRANSPORT



Features:

- stereo CD transport
- equipped with vM Super Clock with low phase distortion and jitter
- digital outputs: XLR, coaxial and optical
- special vM power supplies
- audiophile digital circuitry for optimal soundstage
- highly musical performance, low distortion
- vM remote control
- front plate: silver finish

The Van Medevoort CT260 stereo CD transport is designed for music lovers and to match and connect on the digital input of the vM MA260 or an external DAC like the vM DA466. The same heavy, rigid housing is used to minimize resonances and mechanical distortion. The CD transport mechanism is mounted on a multiple sub chassis with vibration absorption and using an elastic suspension to isolate against acoustic feedback. Only audiophile quality components are used in the power supplies and the digital circuits. The vM Super Clock is placed for perfect timing, but also minimum jitter or phase noise. Extra control options are available, such as repeat or random play, by using the remote control. Next to the gold plated digital coaxial RCA and XLR outputs, for SPDif and AES-EBU, there is also an optical output available.

Specifications:

CD mechanism	vM Teac
conform	Red Book protocol
signal format	16 bit PCM - 44.1 kHz
disc format	CD, CD-R, CD-RW
disc support	80 / 120mm (IEC908)
vM Super Clock	16.9344 MHz
outputs / connectors	3 / XLR, RCA + Optical
output digital	0.5 Vp-p, EBU-XLR 4Vp-p
power supply	115-230 Volt / 50-60 Hz
power consumption	5 / 15 Watt, stby / on
weight	9 kg
size w x h (h+feet) x d	434 x 88 (102) x 390 mm

Options: vM Silver Cable
vM Power line Filter

Van Medevoort
Audio products

Visit our website for more information.
Copyright © 2015 Van Medevoort Audio / The Netherlands
Specifications are subject to change without prior notice.

www.vanmedevoortaudio.nl
contact@vanmedevoortaudio.nl