

CT460

CD TRANSPORT



Features:

- stereo CD transport
- top loader system with exclusive designed stabilizer
- special vM Super Clock with low phase distortion and jitter
- digital outputs Q-Link, XLR, coaxial and optical
- multiple stage vM power supplies
- audiophile digital circuitry for optimal soundstage
- highly musical performance
- remote controlled by RC5
- silver / black finished front plate

The Van Medevoort CT460 stereo CD transport top loader is designed to match the vM DA466 and DA468 D/A converters. The same heavy, rigid housing is used to minimize resonances and mechanical distortion. The CD transport mechanism is mounted on a multiple sub chassis with vibration absorption and using an elastic suspension to isolate against acoustic feedback. Only audiophile quality components are used in the power supplies and the digital circuits. A vM Super Clock is placed for perfect timing, but also minimum jitter and phase distortion. Extra control options are available, such as repeat or random play, by using the remote control. Next to the gold plated digital coaxial RCA and XLR outputs, there is also an optical output available and of course the best (I2S) connection to our converters: vM Q-Link.

\sim					
S'n	മവ	tı	cati	ınr	ve.
ω	C ()		Cal	IV JI	1.

CD mechanism
conform
signal format
disc format
disc support
Q-Link Clock input
outputs / connectors
output SPDif and Q-Link
power supply
power consumption
weight
size w x h (h+feet) x d

CD-Pro2LF metal frame Red Book protocol 16 bit PCM - 44.1 kHz CD, CD-R, CD-RW 80 / 120mm (IEC908) 16.9344 MHz

16.9344 MHz 4 / RCA, XLR + Optical 0.5 Vp-p (EBU-XLR 4Vp-p) 115-230 Volt / 50-60 Hz 20 / 30 Watt – stb / on

11.5 kg

434 x 94 (108) x 390 mm

Options: vM Silver Cable vM Powerline Filter

Van Medevoort Audio products

Visit our website for more information.

Copyright © 2015 Van Medevoort Audio / The Netherlands Specifications are subject to change without prior notice.

www.vanmedevoortaudio.nl contact@vanmedevoortaudio.nl