



VAN MEDEVOORT

MA350

MAIN AMPLIFIER



Features:

- 150 Watt stereo music power
- handles any commercial loudspeaker system
- high slew rate, low distortion
- highly musical performance
- XLR and RCA gold plated input connectors
- protection circuitry
- remote controlled inputs, volume and power
- silver / black finished front plate

The Van Medevoort MA350 integrated stereo amplifier is built with very fast, low-distortion, discrete class 'A' line and power stages and a more than generous power supply section for the highest quality musical performance and best control over your loudspeaker system with any kind of music. The housing is extremely solid with a beautiful finish and only audiophile quality components are used. One input is balanced XLR. A pre-out / main-in is installed to use the MA350 as a separate control and / or power amplifier.

Specifications:

nominal power	> 2x 150 Watt / 8 Ohms
power RMS	> 2x 110 Watt / 8 Ohms
damping factor	1200 - 1500
input impedance	50 kOhms
input level max.	unlimited
channel separation	> 100 dB / 1.5 -100,000 Hz
distortion	< 0.002 % / 1.5 -100,000 Hz
signal to noise ratio	> 100 dB
inputs / connectors	6 / 1x XLR + 5x RCA
outputs / connectors	2 / 5 way binding posts
power supply	115-230 Volt / 50-60 Hz
power consumption	6/21-330 Watt stb/min-max
weight	11.5 kg
size w x h (h+feet) x d	434 x 88 (102) x 410 mm

Options: vM Silver Cable

**Van Medevoort**  
**Audio** products

Visit our website for more information.  
Copyright © 2015 Van Medevoort Audio / The Netherlands  
Specifications are subject to change without prior notice.

[www.vanmedevoortaudio.nl](http://www.vanmedevoortaudio.nl)  
[contact@vanmedevoortaudio.nl](mailto:contact@vanmedevoortaudio.nl)